Product data sheet



GF Uponor MLC pipe cutting tool blade 25-63

1006635

- for MLC pipes



Application information GF Uponor MLC pipe cutting tool blade

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC pipe cutting tool blade 25-63

1006635



Product code

Item no EAN	4021598724372
Item no GF	35001006635
Item no GTIN	04021598724372
Item no LVI	1725978
Item no NOBB	41942085
Item no NRF	5071815
Item no RSK	1873307
Item no VVS	045498364

Dimensions

Item Unit Height	7
Item Unit Length	24
Item Unit Weight	0,004
Item Unit Width	24
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433278
Packaging Height PL1	10
Packaging Length PL1	30
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000006
Packaging Weight PL1	0,005
Packaging Width PL1	20

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+