Product data sheet



GF Uponor MLC bevelling tool 40

1006638

- for MLC pipes





Application information GF Uponor MLC bevelling tool

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bevelling tool 40

1006638





Product code

Item no EAN	4021598300040
Item no GF	35001006638
Item no GTIN	04021598300040
Item no LVI	1725989
Item no NOBB	41942157
Item no NRF	5071825
Item no RSK	1873312
Item no VVS	045498540

Dimensions

Item Unit Height	70
Item Unit Length	110
Item Unit Weight	0,183
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433285
Packaging GTIN PL4	06414905456406
Packaging Height PL1	40
Packaging Height PL4	280
Packaging Length PL1	170
Packaging Length PL4	340
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	1

Packaging Quantity PL4	600
Packaging Type PL1	Plastic_Bag
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000816
Packaging Volume PL4	0,024752
Packaging Weight PL1	0,193
Packaging Weight PL4	134,8
Packaging Width PL1	120
Packaging Width PL4	260

Technical data

Recycling Text Block PL1	Low density polyethylene

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+