Product data sheet



GF Uponor S-Press spare battery UP75

1006949

- for the battery powered pressing machine UP 75
- Not compatible to the Ni-Cd charger unit.



Application information GF Uponor S-Press spare battery UP75

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press spare battery UP75

1006949



Product code

Item no EAN	4021598701311
Item no GF	35001006949
Item no GTIN	04021598701311
Item no LVI	1725916
Item no NOBB	41942252
Item no NRF	5071846
Item no RSK	1873316
Item no VVS	045498076

Dimensions

Item Unit Height	83
Item Unit Length	115
Item Unit Weight	0,64
Item Unit Width	80
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433377
Packaging GTIN PL3	06414905444724
Packaging Height PL1	110
Packaging Height PL3	130
Packaging Length PL1	95
Packaging Length PL3	395
Packaging Material (number) PL1	20
Packaging Material (number) PL3	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material PL3	Corrugated fibreboard

Packaging Material (short) PL1	PAP
Packaging Material (short) PL3	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	12
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Volume PL1	0,0009405
Packaging Volume PL3	0,01976975
Packaging Weight PL1	0,69
Packaging Weight PL3	8,9
Packaging Width PL1	90
Packaging Width PL3	385

Technical data

Recycling Text Block PL1	Corrugated fibreboard
Recycling Text Block PL3	Corrugated fibreboard

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+