Product data sheet



GF Uponor S-Press electric tool w/o jaws UP75

1007082

- Technical specifications:
- Weightl: 3.30 kg
- Nominal voltage: 230 V AC / 50 Hz
- Nominal capacity: 200 Watt
- Press power: ca. 32 kN
- Press duration: ca. 7 sec.





Application information GF Uponor S-Press electric tool w/o jaws UP75

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press electric tool w/o jaws UP75

1007082





Status

Item Available Till date	2026-12-31T00:00:00.000+0100

Product code

Item no EAN	4021598100114
Item no GF	35001007082
Item no GTIN	04021598100114
Item no VVS	045498050

Dimensions

Item Unit Height	320
Item Unit Length	345
Item Unit Weight	3,6
Item Unit Width	67
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905433469
Packaging GTIN PL4	06414900310116
Packaging Height PL1	480
Packaging Height PL4	960
Packaging Length PL1	570
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	20
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,038304
Packaging Volume PL4	0,9216

Packaging Weight PL1	7,12
Packaging Weight PL4	97,72
Packaging Width PL1	140
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+