

Uponor Radi Pipe natural PN6 32x2,9 100m

1008449

- Operating pressure 6 bar
- Coil



Application information Uponor Radi Pipe natural PN6

Specification

- Pipes manufactured from peroxide cross-linked polyethylene (PE-Xa) acc. EN ISO 15875
- EVOH (ethylene vinyl alcohol) layer for oxygen diffusion resistance as per DIN 4726
- Application class 5 - high temperature radiators
- Fire classification E according to DIN EN 13501-1.

Application

- Heating: The permanent operating temperature ranges up to 90°C. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Uponor Radi Pipe natural PN6 32x2,9 100m

1008449



Product code

Item no EAN	7321500044923
Item no GF	35001008449
Item no GTIN	07321500044923
Item no LVI	2012133
Item no NOBB	41949524
Item no NRF	8362313
Item no RSK	2418015
Item no VVS	087230132

Dimensions

Item Unit Height	32
Item Unit Length	1000
Item Unit Weight	0,276
Item Unit Width	32
Item_UOM	m

Measurements

Outer Diameter_do	32
Wall thickness_s	2,9

Packaging

Packaging GTIN PL1	06414905252695
Packaging GTIN PL4	06414905252718
Packaging Height PL1	190
Packaging Height PL4	950
Packaging Length PL1	1160
Packaging Length PL4	1200
Packaging Quantity PL1	100
Packaging Quantity PL4	700
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,255664
Packaging Volume PL4	0,912
Packaging Weight PL1	26,8
Packaging Weight PL4	212,6
Packaging Width PL1	1160
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com