

## Uponor Wipex reducer male x female G4-G3

1009052

- Material: brass
- Female & male thread



### Application information Uponor Wipex reducer male x female

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

#### Certification

- Approvals should be checked by local responsible person

## Uponor Wipex reducer male x female G4-G3

1009052



### Measurements

Cylindric_thread_G	4
Cylindric_thread_G1	3
LENGTH_L	58
z1	30

### Product code

Item no EAN	7331541099011
Item no GF	35001009052
Item no GTIN	07331541099011
Item no NOBB	41946100
Item no NRF	8360739
Item no RSK	2410644
Item no VVS	087836193

### Dimensions

Item Unit Height	60
Item Unit Length	130
Item Unit Weight	1,537
Item Unit Width	130
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905434503
Packaging GTIN PL3	06414905445066
Packaging Height PL1	63
Packaging Height PL3	145
Packaging Length PL1	133
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	6

Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box
Packaging Volume PL1	0,001114407
Packaging Volume PL3	0,0100572
Packaging Weight PL1	1,552
Packaging Weight PL3	9,63
Packaging Width PL1	133
Packaging Width PL3	255

## Documents

Page with all documents 

### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com