Product data sheet



GF Uponor MLC pipe straightening tool 14-25

1010512

- The pipe straightener is not compatible with the Uponor uncoiler
- Fixing has to be managed on site.





Application information GF Uponor MLC pipe straightening tool

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC pipe straightening tool 14-25

1010512





Product code

Item no EAN	4021598016170
Item no GF	35001010512
Item no GTIN	04021598016170
Item no LVI	1725900

Dimensions

Item Unit Height	77
Item Unit Length	230
Item Unit Weight	3,2
Item Unit Width	195
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905434756
Packaging Height PL1	95
Packaging Length PL1	260
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0055575
Packaging Weight PL1	3,6
Packaging Width PL1	225

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+