
Product data sheet




GF Uponor Smart Radi connection unit box 16 h=215

1013134

- Made of polystyrene with removable protective cap (WLS 040)
- Insulation box, flame resistant, B1 acc. to DIN 4102
- 100% acc. EnEV in outer wall





Application information GF Uponor Smart Radi connection unit box

Specification

- Suitable for coated copper pipes (15 × 1 mm), MLCP 16 × 2 mm, PE-Xa and MLC connection lines
- Components made of tin-plated brass, coated brass, coated copper, polystyrene, and PP
- Compatible with S-Press, Q&E, clamp compression adapters and Eurocone interfaces


If not different mentionned:
- Fire-rated cover plates (e.g., EN 13501-1 classes B2 or E depending on model)
- Q&E rings must be ordered separately if not different mentioned


Application

- Connecting radiators to Uponor MLCP or Uni Pipe PLUS heating circuits
- Providing stable, aligned flow and return lines using dedicated adapters and connection boxes
- Interfacing with radiator valves via system-specific compression sets (Danfoss, Heimeier, Oventrop)
- Protecting and guiding pipes at wall or floor penetrations with cover plates and protective sleeves

GF Uponor Smart Radi connection unit box 16 h=215

1013134





Product code

Item no EAN	4021598002852
Item no GF	35001013134
Item no GTIN	04021598002852

Dimensions

Item Unit Height	100
Item Unit Length	260
Item Unit Weight	0,19
Item Unit Width	260
Item_UOM	pce

Packaging

Packaging GTIN PL3	06414905445219
Packaging GTIN PL4	06414905487622
Packaging Height PL3	500
Packaging Height PL4	1880
Packaging Length PL3	520
Packaging Length PL4	1200
Packaging Quantity PL3	10
Packaging Quantity PL4	240
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL3	0,0754
Packaging Volume PL4	1,8048
Packaging Weight PL3	2,23
Packaging Weight PL4	66,9
Packaging Width PL3	290

Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+