Product data sheet



GF Uponor MLC bending spring inside 25

1013737

- bending spring for Uponor Uni Pipe PLUS and MLC pipes.



Application information GF Uponor MLC bending spring inside

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bending spring inside 25

1013737



Product code

Item no EAN	4021598700949
Item no GF	35001013737
Item no GTIN	04021598700949
Item no LVI	1725955
Item no NOBB	41942214
Item no NRF	5071836
Item no RSK	1873302
Item no VVS	045498625

Dimensions

Item Unit Height	17
Item Unit Length	620
Item Unit Weight	0,63
Item Unit Width	17
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905538119
Packaging GTIN PL3	06414905483525
Packaging Height PL1	35
Packaging Height PL3	210
Packaging Length PL1	180
Packaging Length PL3	700
Packaging Material (number) PL1	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material (short) PL1	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	50
Packaging Type PL1	Piece

Packaging Type PL3	Box
Packaging Volume PL1	0,001134
Packaging Volume PL3	0,03087
Packaging Weight PL1	0,63
Packaging Weight PL3	32,176
Packaging Width PL1	180
Packaging Width PL3	210

Technical data

Recycling Text Block PL1	Corrugated fibreboard

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+