Product data sheet



GF Uponor MLC pipe cutting 63-110

1014334

- for MLC pipes



Application information GF Uponor MLC pipe cutting

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC pipe cutting 63-110

1014334



Product code

Item no EAN	4021598002357
Item no GF	35001014334
Item no GTIN	04021598002357
Item no LVI	1725984
Item no NOBB	41942615
Item no NRF	5071921
Item no RSK	1875699
Item no VVS	045498710

Dimensions

Item Unit Height	135
Item Unit Length	205
Item Unit Weight	3,6
Item Unit Width	330
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905435371
Packaging Height PL1	255
Packaging Length PL1	490
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,01811775
Packaging Weight PL1	4,4
Packaging Width PL1	145

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+