


Uponor S-Press coupling 14-14

1015154

- Made of tin-plated brass
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code



Application information Uponor S-Press coupling

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
- AENOR

Uponor S-Press coupling 14-14

1015154



Product code

Item no EAN	4021598302884
Item no GF	35001015154
Item no GTIN	04021598302884

Dimensions

Item Unit Height	22
Item Unit Length	55
Item Unit Weight	0,032
Item Unit Width	22
Item_UOM	pce

Measurements

LENGTH_L	54
Length (l1)	21,3
Length (l2)	21,3
z1	11,4

Packaging

Packaging GTIN PL1	06414905436293
Packaging GTIN PL3	06414905446162
Packaging GTIN PL4	06414905489800
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	570
Packaging Length PL1	87
Packaging Length PL3	277
Packaging Length PL4	1120
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	7680

Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000518781
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,4775232
Packaging Weight PL1	0,339
Packaging Weight PL3	2,812
Packaging Weight PL4	271,584
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	748

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com