Product data sheet



GF Uponor S-Press battery Mini

1015703

- Battery: 9.6V for Uponor battery pressing tool Mini KSP0.



Application information GF Uponor S-Press battery Mini

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press battery Mini

1015703





Product code

Item no EAN	4021598021211
Item no GF	35001015703
Item no GTIN	04021598021211
Item no LVI	1725915
Item no NOBB	41942600
Item no NRF	5071924
Item no RSK	1874232
Item no VVS	045498406

Dimensions

Item Unit Height	57
Item Unit Length	85
Item Unit Weight	0,421
Item Unit Width	75
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436910
Packaging Height PL1	85
Packaging Length PL1	120
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00102
Packaging Weight PL1	0,477
Packaging Width PL1	100

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+