Product data sheet



GF Uponor MLC bevelling tool 16/20/25

1015739

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.



Application information GF Uponor MLC bevelling tool

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bevelling tool 16/20/25

1015739



Product code

Item no EAN	4021598303379
Item no GF	35001015739
Item no GTIN	04021598303379
Item no LVI	1725983
Item no NOBB	41942180
Item no NRF	5071831
Item no RSK	1873357
Item no VVS	045498526

Dimensions

Item Unit Height	29
Item Unit Length	104
Item Unit Weight	0,13
Item Unit Width	99
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436927
Packaging GTIN PL3	06414905446520
Packaging GTIN PL4	06414900310130
Packaging Height PL1	30
Packaging Height PL3	205
Packaging Height PL4	1566
Packaging Length PL1	105
Packaging Length PL3	385
Packaging Length PL4	1200
Packaging Material (number) PL1	20

Packaging Material (number) PL3	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material PL3	Corrugated fibreboard
Packaging Material (short) PL1	PAP
Packaging Material (short) PL3	PAP
Packaging Quantity PL1	1
Packaging Quantity PL3	60
Packaging Quantity PL4	1440
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000315
Packaging Volume PL3	0,0236775
Packaging Volume PL4	1,50336
Packaging Weight PL1	0,14
Packaging Weight PL3	8,35
Packaging Weight PL4	212,2
Packaging Width PL1	100
Packaging Width PL3	300
Packaging Width PL4	800

Technical data

Recycling Text Block PL1	Corrugated fibreboard
Recycling Text Block PL3	Corrugated fibreboard

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+