Product data sheet



GF Uponor MLC bevelling tool 20

1015749

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.
- Supplied with manual toggle. Without manual toggle to be used as attachment for self-driving screw with tapping screw thread.



Application information GF Uponor MLC bevelling tool

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bevelling tool 20

1015749



Product code

Item no EAN	4021598303027
Item no GF	35001015749
Item no GTIN	04021598303027
Item no LVI	1725986
Item no NOBB	41942123
Item no NRF	5071822
Item no RSK	1873309
Item no VVS	045498520

Dimensions

Item Unit Height	34
Item Unit Length	115
Item Unit Weight	0,136
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436934
Packaging GTIN PL4	06414905490455
Packaging Height PL1	40
Packaging Height PL4	280
Packaging Length PL1	120
Packaging Length PL4	340
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	1

Packaging Quantity PL4	1200
Packaging Type PL1	Plastic_Bag
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000576
Packaging Volume PL4	0,024752
Packaging Weight PL1	0,141
Packaging Weight PL4	188,2
Packaging Width PL1	120
Packaging Width PL4	260

Technical data

Recycling Text Block PL1	Low density polyethylene

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+