Product data sheet



GF Uponor MLC bevelling tool 25

1015756

- For bevelling the Uponor Uni Pipe PLUS and MLC pipes.
- Supplied with manual toggle. Without manual toggle to be used as attachment for self-driving screw with tapping screw thread.



Application information GF Uponor MLC bevelling tool

Specification

- Oxygen diffusion resistant multi-layer composite pipe(PE-RT - adhesive - longitudinally welded aluminium - adhesive - PE-RT)
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor MLC bevelling tool 25

1015756



Product code

Item no EAN	4021598303034
Item no GF	35001015756
Item no GTIN	04021598303034
Item no LVI	1725987
Item no NOBB	41942138
Item no NRF	5071823
Item no RSK	1873310
Item no VVS	045498525

Dimensions

Item Unit Height	38
Item Unit Length	120
Item Unit Weight	0,21
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436941
Packaging GTIN PL4	06414905490462
Packaging Height PL1	40
Packaging Height PL4	280
Packaging Length PL1	130
Packaging Length PL4	340
Packaging Material (number) PL1	4
Packaging Material PL1	Low density polyethylene
Packaging Material (short) PL1	LDPE
Packaging Quantity PL1	1

Packaging Quantity PL4	960
Packaging Type PL1	Plastic_Bag
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000624
Packaging Volume PL4	0,024752
Packaging Weight PL1	0,22
Packaging Weight PL4	226,6
Packaging Width PL1	120
Packaging Width PL4	260

Technical data

Recycling Text Block PL1	Low density polyethylene

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+