Product data sheet



GF Uponor S-Press manual tool w/o inserts 14-20

1015764

- in conjunction with exchangeable inserts
- Supplied in case without exchangeable inserts



Application information GF Uponor S-Press manual tool w/o inserts

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press manual tool w/o inserts 14-20

1015764



Product code

Item no EAN	4021598015005
Item no GF	35001015764
Item no GTIN	04021598015005
Item no LVI	1725902
Item no NOBB	41942365
Item no NRF	5071861
Item no RSK	1876996
Item no VVS	045498021

Dimensions

Item Unit Height	27
Item Unit Length	505
Item Unit Weight	1,8
Item Unit Width	125
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905436965
Packaging GTIN PL4	06414900310147
Packaging Height PL1	50
Packaging Height PL4	450
Packaging Length PL1	520
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	100
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,00494
Packaging Volume PL4	0,432
Packaging Weight PL1	3,6
Packaging Weight PL4	206,8
Packaging Width PL1	190
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+