


GF Uponor Ecoflex Varia Pipe Single 25x2,3 /90

1018230

- Heating and Cooling
- One medium pipe PE-Xa with oxygen barrier, SDR 11
- Max. load 6 bar / 95°C
- PEX foam, HDPE casing



Application information GF Uponor Ecoflex Thermo Pipe mini

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632 and EN 17414.
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11), oxygen tightness based on EN 15632.
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

NOTE:

Ecoflex Varia pipes listed in Ecoflex Thermo product line. Varia will be renamed as Thermo beginning of 2027

Application


- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

GF Uponor Ecoflex Varia Pipe Single 25x2,3 /90

1018230



Measurements

Bending radius M	0,25
Outer Diameter_do	90
Outer Diameter_do1	25
Wall thickness_s1	2,3

Product code

Item no EAN	6414905201914
Item no GF	35001018230
Item no GTIN	06414905201914
Item no VVS	087807425

Dimensions

Item Unit Height	90
Item Unit Length	1000
Item Unit Weight	1,02
Item Unit Width	90
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905437610
Packaging Height PL1	1600
Packaging Length PL1	700
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	1,792
Packaging Weight PL1	204
Packaging Width PL1	1600

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com