

Uponor Wipex flange F100/8-180/G4

1018365

- Cylindric thread G" with sealing ring
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DR = dezincification resistance brass



Application information Uponor Wipex flange

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex flange F100/8-180/G4

1018365

**Measurements**

Cylindric_thread_G	4
Outer Diameter_do	220
Z Measurement k	180

Product code

Item no EAN	7331541099356
Item no GF	35001018365
Item no GTIN	07331541099356
Item no NOBB	41946172
Item no NRF	8360757
Item no RSK	2410651
Item no VVS	087844091

Dimensions

Item Unit Height	32
Item Unit Length	223
Item Unit Weight	4,441
Item Unit Width	223
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905437955
Packaging GTIN PL3	06414905446773
Packaging Height PL1	34
Packaging Height PL3	155
Packaging Length PL1	225
Packaging Length PL3	272
Packaging Quantity PL1	1
Packaging Quantity PL3	3
Packaging Type PL1	Plastic_Bag

Packaging Type PL3	Box
Packaging Volume PL1	0,00172125
Packaging Volume PL3	0,01054
Packaging Weight PL1	4,451
Packaging Weight PL3	13,682
Packaging Width PL1	225
Packaging Width PL3	250

Documents

Page with all documents

↓

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com