Product data sheet



GF Uponor Vario PLUS manifold w. valve LS 4x3/4 Euro

1030581

- with valve and eurocone thread



Application information GF Uponor Vario PLUS manifold w. valve

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing or connection from below with optional elbowset
- Supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared places for room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator:
- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

GF Uponor Vario PLUS manifold w. valve LS 4x3/4 Euro

1030581



Product code

Item no EAN	4016203841247
Item no GF	35001030581
Item no GTIN	04016203841247
Item no LVI	2025026
Item no NOBB	42496035
Item no NRF	8362715
Item no RSK	2418996
Item no VVS	087605134

Dimensions

Item Unit Height	180
Item Unit Length	220
Item Unit Weight	0,955
Item Unit Width	45
Item_UOM	pr

Packaging

Packaging GTIN PL1	06414905264964
Packaging GTIN PL4	06414905264971
Packaging Height PL1	137
Packaging Height PL4	1500
Packaging Length PL1	225
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	225
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,002620125
Packaging Volume PL4	1,44
Packaging Weight PL1	1,005
Packaging Weight PL4	251,125
Packaging Width PL1	85
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+