

## Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

**1030584**

- Modules for Vario Plus manifold
- with flowmeter



### Application information Uponor Vario PLUS manifold flowmeter

#### Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing or connection from below with optional elbowset
- Supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared places for room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

#### Application

- For underfloor heating and cooling
- Can be combined with actuators MT 30x1,5

#### Certification

- CE

## Uponor Vario PLUS manifold flowmeter FM 4x3/4 Euro

1030584



### Measurements

Cylindric_thread_G	0,75
LENGTH_L	224
Length (l1)	200
Length (l2)	119
Length (l3)	63
Z Measurement b	50
Z3	50

### Product code

Item no EAN	4016203841346
Item no GF	35001030584
Item no GTIN	04016203841346

### Dimensions

Item Unit Height	180
Item Unit Length	220
Item Unit Weight	1,002
Item Unit Width	45
Item_UOM	pr

### Packaging

Packaging GTIN PL1	06414905265022
Packaging GTIN PL4	06414905265039
Packaging Height PL1	182
Packaging Height PL4	1500
Packaging Length PL1	225
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	135
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00348075
Packaging Volume PL4	1,44
Packaging Weight PL1	1,052
Packaging Weight PL4	167,02
Packaging Width PL1	85
Packaging Width PL4	800

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com