

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585

- Modules for Vario Plus manifold
- with flowmeter



Application information Uponor Vario PLUS manifold flowmeter

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing or connection from below with optional elbowset
- Supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared places for room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator:

- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

Uponor Vario PLUS manifold flowmeter FM 6x3/4 Euro

1030585



Measurements

Cylindric_thread_G	0,75
LENGTH_L	324
Length (l1)	300
Length (l2)	119
Length (l3)	63
Z Measurement b	50
Z3	50

Product code

Item no EAN	4016203841360
Item no GF	35001030585
Item no GTIN	04016203841360

Dimensions

Item Unit Height	180
Item Unit Length	320
Item Unit Weight	1,49
Item Unit Width	45
Item_UOM	pr

Packaging

Packaging GTIN PL1	06414905265046
Packaging GTIN PL4	06414905265053
Packaging Height PL1	182
Packaging Height PL4	1500
Packaging Length PL1	325
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	93
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00502775
Packaging Volume PL4	1,44
Packaging Weight PL1	1,54
Packaging Weight PL4	168,22
Packaging Width PL1	85
Packaging Width PL4	800

Documents

Page with all documents

↓

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com