Product data sheet



GF Uponor S-Press adapter male thread MT 63-R2"

1032895

- Made of tin-plated DR brass (lead-free)
- Fast installation with easy bevel and without calibration
- Colour code



Application information GF Uponor S-Press adapter male thread MT

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press adapter male thread MT 63-R2"

1032895



Product code

Item no EAN	6414905220748
Item no GF	35001032895
Item no GTIN	06414905220748
Item no LVI	1720166
Item no NRF	5114378
Item no RSK	1899466
Item no VVS	045481063

Dimensions

Item Unit Height	72
Item Unit Length	111
Item Unit Weight	0,786
Item Unit Width	72
Item_UOM	pce

Measurements

LENGTH_L	111
Length (l1)	28
Length (l2)	60,6
Male_thread_R	2
Z Measurement d	63
z1	22

Packaging

Packaging GTIN PL1	06414905439775
Packaging GTIN PL4	06414905491551
Packaging Height PL1	83
Packaging Height PL4	642

Packaging Length PL1	150
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	336
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0014193
Packaging Volume PL4	0,61632
Packaging Weight PL1	0,842
Packaging Weight PL4	306,912
Packaging Width PL1	114
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+