


Uponor S-Press PLUS elbow PPSU 16-16

1039929

- Material: PPSU



Application information Uponor S-Press PLUS elbow PPSU

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS elbow PPSU 16-16

1039929



Product code

Item no EAN	6414905228683
Item no GF	35001039929
Item no GTIN	06414905228683
Item no LVI	1720686
Item no NOBB	55171457
Item no NRF	5114381
Item no RSK	1896525
Item no VVS	087430116

Dimensions

Item Unit Height	44
Item Unit Length	44
Item Unit Weight	0,01704
Item Unit Width	22
Item_UOM	pce

Measurements

Length (l1)	33
Length (l2)	33
z1	13,1
z2	13,1

Packaging

Packaging GTIN PL1	06414905634873
Packaging GTIN PL3	06414905425488
Packaging GTIN PL4	06414905289424
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	714
Packaging Length PL1	176

Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,378
Packaging Weight PL3	1,712
Packaging Weight PL4	189,352
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com