
Product data sheet




GF Uponor S-Press PLUS tee reducer PPSU 32-20-32

1039959

- Material: PPSU
- Fixed stainless steel sleeve





Application information GF Uponor S-Press PLUS tee reducer PPSU

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification


- Approvals by local OM.

E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS tee reducer PPSU 32-20-32

1039959





Product code

Item no EAN	6414905228973
Item no GF	35001039959
Item no GTIN	06414905228973
Item no LVI	1720716
Item no NOBB	55171722
Item no NRF	5114414
Item no RSK	1807995
Item no VVS	087443132

Dimensions

Item Unit Height	63.65
Item Unit Length	102
Item Unit Weight	0,097
Item Unit Width	39.3
Item_UOM	pce

Measurements

Length (l1)	51
Length (l2)	44
Length (l3)	51
z1	23,2
Z2	22,7
Z3	23,2

Packaging

Packaging GTIN PL1	06414905480043
Packaging GTIN PL3	06414905528738
Packaging GTIN PL4	06414905480067

Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,524
Packaging Weight PL3	2,373
Packaging Weight PL4	137,894
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+