

## Uponor RS lock pin RS3 grey

**1042922**

- made of plastic
- to lock the RS insert to the RS base part.



### Application information Uponor RS lock pin

#### Specification

- with fixed press sleeve
- stop ring
- colour code
- Test safety

#### Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

#### Certification

- Approvals by local OM.

E.g.

- DVGW
- AENOR

## Uponor RS lock pin RS3 grey

1042922



## Product code

|              |                |
|--------------|----------------|
| Item no EAN  | 4021598106864  |
| Item no GF   | 35001042922    |
| Item no GTIN | 04021598106864 |
| Item no LVI  | 1720627        |
| Item no NRF  | 5079073        |
| Item no RSK  | 1877272        |
| Item no VVS  | 045459122      |

## Dimensions

|                  |       |
|------------------|-------|
| Item Unit Height | 8     |
| Item Unit Length | 280   |
| Item Unit Weight | 0,004 |
| Item Unit Width  | 8     |
| Item_UOM         | pce   |

## Packaging

|                                 |                          |
|---------------------------------|--------------------------|
| Packaging GTIN PL1              | 06414905458851           |
| Packaging Height PL1            | 15                       |
| Packaging Length PL1            | 320                      |
| Packaging Material (number) PL1 | 4                        |
| Packaging Material PL1          | Low density polyethylene |
| Packaging Material (short) PL1  | LDPE                     |
| Packaging Quantity PL1          | 10                       |
| Packaging Type PL1              | Plastic_Bag              |
| Packaging Volume PL1            | 0,00096                  |
| Packaging Weight PL1            | 0,06                     |
| Packaging Width PL1             | 200                      |

## Technical data

|                          |                          |
|--------------------------|--------------------------|
| Recycling Text Block PL1 | Low density polyethylene |
|--------------------------|--------------------------|

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211  
E  
communications@georgfischer.  
com