Product data sheet



GF Uponor S-Press chain 90

1046543

- pressing chain to be used together with the Base unit to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Application information GF Uponor S-Press chain

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press chain 90

1046543



Product code

Item no EAN	4021598112292
Item no GF	35001046543
Item no GTIN	04021598112292
Item no LVI	1725949
Item no NOBB	48505361
Item no NRF	5071928
Item no RSK	1877983
Item no VVS	045499543

Dimensions

Item Unit Height	60
Item Unit Length	155
Item Unit Weight	3,29
Item Unit Width	155
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905460250
Packaging GTIN PL4	06414905493296
Packaging Height PL1	85
Packaging Height PL4	600
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	72
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,0047515
Packaging Volume PL4	0,576
Packaging Weight PL1	3,73
Packaging Weight PL4	268,56
Packaging Width PL1	215
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+