Product data sheet



GF Uponor S-Press chain 110

1046544

- pressing chain to be used together with the Base unit to press Uponor MLC press fittings 63 - 110 in conjunction with the pressing tool UP 110, UP 75 and UP 75 EL



Application information GF Uponor S-Press chain

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press chain 110

1046544



Product code

Item no EAN	4021598112308
Item no GF	35001046544
Item no GTIN	04021598112308
Item no LVI	1725950
Item no NOBB	48505380
Item no NRF	5071929
Item no RSK	1877984
Item no VVS	045499544

Dimensions

Item Unit Height	59
Item Unit Length	170
Item Unit Weight	3,88
Item Unit Width	170
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905460267
Packaging GTIN PL4	06414905493302
Packaging Height PL1	85
Packaging Height PL4	900
Packaging Length PL1	320
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	54
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,007208
Packaging Volume PL4	0,864
Packaging Weight PL1	4,51
Packaging Weight PL4	243,54
Packaging Width PL1	265
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+