
Product data sheet




GF Uponor S-Press adapter male thread MT 40-R1 1/2"

1046902

- Made of tin-plated DR brass (lead-free)
- Fast installation with easy bevel and without calibration
- Colour code





Application information GF Uponor S-Press adapter male thread MT

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


- if not different mentioned:
Male and female threads acc.to EN 10226-1.


Certification

- Approvals by local OM.
E.g.
- DVGW
- AENOR

GF Uponor S-Press adapter male thread MT 40-R1 1/2"

1046902





Product code

Item no EAN	4021598113992
Item no GF	35001046902
Item no GTIN	04021598113992
Item no LVI	1720929
Item no NRF	1627543
Item no VVS	045481042

Dimensions

Item Unit Height	54
Item Unit Length	72
Item Unit Weight	0,311
Item Unit Width	54
Item_UOM	pce

Measurements

LENGTH_L	72
Length (l1)	20
Length (l2)	37,5
Male_thread_R	1 1/2
Z Measurement d	40
z1	14,5

Packaging

Packaging GTIN PL1	06414905401437
Packaging GTIN PL4	06414905401444
Packaging Height PL1	89
Packaging Height PL4	560
Packaging Length PL1	176

Packaging Length PL4	1120
Packaging Quantity PL1	5
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,4691456
Packaging Weight PL1	2,409
Packaging Weight PL4	468,48
Packaging Width PL1	135
Packaging Width PL4	748

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+