

Uponor S-Press adapter male thread MT 50-R2"

1046906

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Application information Uponor S-Press adapter male thread MT

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:

Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press adapter male thread MT 50-R2"

1046906

**Product code**

Item no EAN	4021598114036
Item no GF	35001046906
Item no GTIN	04021598114036
Item no VVS	045481054

Dimensions

Item Unit Height	86
Item Unit Length	67
Item Unit Weight	0,759
Item Unit Width	67
Item_UOM	pce

Measurements

LENGTH_L	83,5
Length (l1)	24
Length (l2)	37,5
Male_thread_R	2
Z Measurement d	50
z1	22

Packaging

Packaging GTIN PL1	06414905401512
Packaging GTIN PL4	06414905401529
Packaging Height PL1	90
Packaging Height PL4	570
Packaging Length PL1	175
Packaging Length PL4	1120
Packaging Quantity PL1	3
Packaging Quantity PL4	576
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00212625
Packaging Volume PL4	0,4775232
Packaging Weight PL1	2,377
Packaging Weight PL4	481,384
Packaging Width PL1	135
Packaging Width PL4	748

Documents

Page with all documents

↓

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com