

Uponor Base thermostat T-24 flush 230V

1058423

- printed scale on dial thermostat for flush installation
 - simple on/off control (bimetall)
 - setting range can be limited mechanically by moving pins under the dial
 - powered by base unit (Uponor Base controller X-23)
 - setpoint range: +5°C ... +30°C
 - wire: 4x 1.5mm²
 - max. cable length: 100m
 - protection class: IP30
 - color: pure white, glossy
- Consisting of:
- Uponor Base thermostat flush T-24 230V
 - outer frame 81x85x44.5mm
 - cover 50x50mm



Application information Uponor Base thermostat T-24 flush

Specification

- 230V standard wiring
- common wiring method and controls logic
- easy integration to standard on/off time control
- optional: pump logic

Application

- wired room temperature control for radiant heating

Certification

- CE, UKCA

Uponor Base thermostat T-24 flush 230V

1058423



Product code

Item no EAN	7321500053390
Item no GF	35001058423
Item no GTIN	07321500053390

Dimensions

Item Unit Height	35
Item Unit Length	80
Item Unit Weight	0,08
Item Unit Width	80
Item_UOM	pce

Measurements

LENGTH_L	80
Z Measurement h	35
Z Measurement w	80

Packaging

Packaging GTIN PL1	06414905463206
Packaging Height PL1	60
Packaging Length PL1	87
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00045414
Packaging Weight PL1	0,18
Packaging Width PL1	87

Documents

Page with all documents



www.uponor.com