


GF Uponor Uni Pipe PLUS white 32x3,0 50m

1059583

- coil
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier



Application information GF Uponor Uni Pipe PLUS white

Specification

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive – seamless aluminium/longitudinally welded aluminium - adhesive - PE-RT) produced using SACP and OWC-technology.
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application


- Tested/Approved according EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar
- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

GF Uponor Uni Pipe PLUS white 32x3,0 50m

1059583



Product code

Item no EAN	4021598121317
Item no GF	35001059583
Item no GTIN	04021598121317
Item no LVI	1720144
Item no NOBB	48167295
Item no NRF	5072096
Item no RSK	2004928
Item no VVS	087480332

Dimensions

Item Unit Height	32
Item Unit Length	1000
Item Unit Weight	0,379
Item Unit Width	32
Item_UOM	m

Measurements

Length	50
Outer Diameter_do	32
Wall thickness_s	3

Packaging

Packaging GTIN PL1	06414905412181
Packaging GTIN PL4	06414905412198
Packaging Height PL1	205
Packaging Height PL4	2000
Packaging Length PL1	1140
Packaging Length PL4	1140
Packaging Quantity PL1	50
Packaging Quantity PL4	400

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,266418
Packaging Volume PL4	2,5992
Packaging Weight PL1	21,641
Packaging Weight PL4	183,128
Packaging Width PL1	1140
Packaging Width PL4	1140

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com