



Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

1060058

- Connection of PE-Xa pipe to Uponor MLC pipe.
- 6 bar
- DR = dezincification resistance brass



Application information Uponor Wipex adapter S-Press PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- O-ring sealing between Wipex coupling and base fitting connectors
- Bolt set for couplers include a hex socket bolt in stainless steel and the nut as well as washer from brass
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Supra Standard
- Connection of PE and PE-Xa medium pipe to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification

- Approvals should be checked by local responsible person

Uponor Wipex adapter S-Press PN6 32x2,9-32x3,0

1060058



Status

Item Available Till date

2026-12-31T00:00:00.000+0100

Product code

Item no EAN	4021598121669
Item no GF	35001060058
Item no GTIN	04021598121669

Dimensions

Item Unit Height	45
Item Unit Length	48
Item Unit Weight	0,244
Item Unit Width	65
Item_UOM	pce

Measurements

LENGTH_L	66
Length (l1)	30
Length (l2)	26
z1	10

Packaging

Packaging GTIN PL1	06414905412389
Packaging GTIN PL3	06414905412396
Packaging Height PL1	48
Packaging Height PL3	145
Packaging Length PL1	51
Packaging Length PL3	268
Packaging Quantity PL1	1
Packaging Quantity PL3	25
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000166464
Packaging Volume PL3	0,009715
Packaging Weight PL1	0,253
Packaging Weight PL3	6,28
Packaging Width PL1	68
Packaging Width PL3	250

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com