Product data sheet



GF Uponor Vario PLUS insulation kit

1063207

- Insulation thickness 19 mm, 0,038 W/mK
- Length 665 mm
- Fire classification BL-s3,do (EN 13501-1)





Application information GF Uponor Vario PLUS insulation kit

Specification

- Modular fibre glass reinforced polyamide manifold with 1,3,4,6 loops for connection with basic kit
- Connection right or left with flat sealing or connection from below with optional elbowset
- Supply with lockshield (LS) valve for balancing with adjusting ring or supply with Flowmeter (FM) for balancing
- Shut-off and flow view
- Adjusting ring for balancing without tools
- Prepared places for room name labels
- Return with valves and caps, prepared for actuators
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 225 mm

Actuator:
- NC (normally closed) = closes without power

Application

- for underfloor heating and cooling
- combineable with actuators MT 30x1,5

Certification

- CE

GF Uponor Vario PLUS insulation kit

1063207





Product code

Item no EAN	4021598124400
Item no GF	35001063207
Item no GTIN	04021598124400
Item no RSK	2419859
Item no VVS	087604200

Dimensions

Item Unit Height	55
Item Unit Length	655
Item Unit Weight	0,32
Item Unit Width	190
Item_UOM	set

Packaging

Packaging GTIN PL3	06414905450404
Packaging Height PL3	200
Packaging Length PL3	800
Packaging Quantity PL3	1
Packaging Type PL3	Box
Packaging Volume PL3	0,128
Packaging Weight PL3	0,323
Packaging Width PL3	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+