

GF Uponor Fluvia T thermostat Push-23, KRS-6

1063461

- for Push 23



Application information GF Uponor Fluvia T thermostat Push-23, KRS-6

Specification

- Integrated pump: Q: 0,1 - 0,4 m³/h, H: 0,2 - 1,1 m, Phyd< 1W
- Bracket for left- or right installation
- Air bleed screw
- Secondary circuit temp. range 20-50°C
- Balancing valve
- Secondary loop 3/4" eurocone
- Primary valves with clampconnection for CU-Pipe 15mm

Application

- For control of UFH in small zones
- Max. primary temperature: 90°C
- Max. secondary temperature: 55°C

GF Uponor Fluvia T thermostat Push-23, KRS-6

1063461



Status

Item Available From date

2025-05-03

Product code

Item no EAN	4016203775603
Item no GF	35001063461
Item no GTIN	04016203775603
Item no NRF	8361187
Item no VVS	381111800

Dimensions

Item Unit Height	55
Item Unit Length	80
Item Unit Weight	0,221
Item Unit Width	55
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905413416
Packaging Height PL1	75
Packaging Length PL1	105
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,000669375
Packaging Weight PL1	0,271
Packaging Width PL1	85

Documents

Page with all documents

communications@georgfischer.
com