


Uponor S-Press PLUS adapter male thread 32-R1"MT

1070509

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS adapter male thread

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS adapter male thread 32-R1"MT

1070509



Product code

Item no EAN	6414905218295
Item no GF	35001070509
Item no GTIN	06414905218295
Item no LVI	1720179
Item no NOBB	55171832
Item no NRF	5114435
Item no RSK	1899418
Item no VVS	045481382

Dimensions

Item Unit Height	38
Item Unit Length	58
Item Unit Weight	0,134
Item Unit Width	38
Item_UOM	pce

Measurements

LENGTH_L	57,5
Length (l1)	14,5
Length (l2)	28,3
Male_thread_R	1
z1	14,7

Packaging

Packaging GTIN PL1	06414905468270
Packaging GTIN PL3	06414905424047
Packaging GTIN PL4	06414905499205
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708

Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	40
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	0,877
Packaging Weight PL3	7,276
Packaging Weight PL4	368,16
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com