


Uponor S-Press PLUS elbow female thread 25-Rp1"FT

1070543

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS elbow female thread

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS elbow female thread 25-Rp1"FT

1070543



Measurements

Female thread Rp	1
Length (l1)	44,5
Length (l2)	53,8
z1	25,4
z2	25,5

Product code

Item no EAN	6414905218639
Item no GF	35001070543
Item no GTIN	06414905218639
Item no LVI	1720731
Item no NOBB	55172142
Item no NRF	5114472
Item no RSK	1896545
Item no VVS	045472315

Dimensions

Item Unit Height	61
Item Unit Length	74
Item Unit Weight	0,228
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905279951
Packaging GTIN PL3	06414905424313
Packaging GTIN PL4	06414905279975
Packaging Height PL1	89
Packaging Height PL3	95
Packaging Height PL4	714

Packaging Length PL1	135
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001045305
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	1,206
Packaging Weight PL3	5,024
Packaging Weight PL4	490,56
Packaging Width PL1	87
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com