


Uponor S-Press PLUS tee reducer 20-16-20

1070568

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS tee reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press PLUS tee reducer 20-16-20

1070568



Product code

Item no EAN	6414905218882
Item no GF	35001070568
Item no GTIN	06414905218882
Item no LVI	1720750
Item no NOBB	55172335
Item no NRF	5114493
Item no RSK	1808012
Item no VVS	045476241

Dimensions

Item Unit Height	48.7
Item Unit Length	70.5
Item Unit Weight	0,095
Item Unit Width	26
Item_UOM	pce

Measurements

Length (l1)	35,3
Length (l2)	35,8
Length (l3)	35,3
z1	14
z2	16
z3	14

Packaging

Packaging GTIN PL1	06414905291700
Packaging GTIN PL3	06414905424504
Packaging GTIN PL4	06414905291724
Packaging Height PL1	89
Packaging Height PL3	188

Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL3	80
Packaging Quantity PL4	3840
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	1,939
Packaging Weight PL3	8,016
Packaging Weight PL4	410,4
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com