


GF Uponor S-Press PLUS tee female thread FT 20-Rp1/2"-20

1070596

- Made of tin-plated DR brass (lead-free)



Application information GF Uponor S-Press PLUS tee female thread FT

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

GF Uponor S-Press PLUS tee female thread FT 20-Rp1/2"-20

1070596



Measurements

Female thread Rp	1/2
Length (l1)	40
Length (l2)	35,3
Length (l3)	40
z1	18,7
z2	20,3
z3	18,7

Product code

Item no EAN	6414905219162
Item no GF	35001070596
Item no GTIN	06414905219162
Item no LVI	1720770
Item no NOBB	55172532
Item no NRF	5114515
Item no RSK	1808032
Item no VVS	045478239

Dimensions

Item Unit Height	48.2
Item Unit Length	80
Item Unit Weight	0,134
Item Unit Width	26
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905429301
Packaging GTIN PL3	06414905429318
Packaging GTIN PL4	06414905429325
Packaging Height PL1	89

Packaging Height PL3	188
Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL3	60
Packaging Quantity PL4	2880
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	2,09
Packaging Weight PL3	8,49
Packaging Weight PL4	431,52
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com