


Uponor S-Press PLUS adapter swivel nut 20-G1/2"SN

1070604

- Made of tin-plated DR brass
- Releasable screw connector for connection to on-wall fittings, filters and shut-off valves
- Thread acc. to EN ISO 228-1.



Application information Uponor S-Press PLUS adapter swivel nut

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS adapter swivel nut 20-G1/2"SN

1070604



Measurements

Cylindric_thread_G	0,5
LENGTH_L	59,4
Length (l1)	8,4
Length (l2)	21,3
z1	29,7

Product code

Item no EAN	6414905219247
Item no GF	35001070604
Item no GTIN	06414905219247
Item no LVI	1720778
Item no NOBB	55172615
Item no NRF	5114524
Item no RSK	1899453
Item no VVS	045483239

Dimensions

Item Unit Height	27
Item Unit Length	50.5
Item Unit Weight	0,083
Item Unit Width	26
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905468676
Packaging GTIN PL2	06414905442768
Packaging GTIN PL4	06414905499601
Packaging Height PL1	32
Packaging Height PL2	89
Packaging Height PL4	678

Packaging Length PL1	56
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	20
Packaging Quantity PL4	3840
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000055552
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,084
Packaging Weight PL2	1,699
Packaging Weight PL4	361,92
Packaging Width PL1	31
Packaging Width PL2	135
Packaging Width PL4	800

Documents

Page with all documents 

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com