
Product data sheet



GF Uponor S-Press PLUS adapter swivel nut 32-G1 1/4"SN

1070610

- Made of tin-plated DR brass (lead-free)
- Releasable screw connector for connection to on-wall fittings, filters and shut-off valves
- Thread acc. to EN ISO 228-1.



Application information GF Uponor S-Press PLUS adapter swivel nut

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with insprection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:
- Male and female threads acc.to EN 10226-1.


Certification

- Approvals by local OM.

E.g.
- DVGW
- AENOR

GF Uponor S-Press PLUS adapter swivel nut 32-G1 1/4"SN

1070610



Measurements

Cylindric_thread_G	1 1/4
LENGTH_L	58,5
Length (l1)	8,5
Length (l2)	28,3
z1	21,7

Product code

Item no EAN	6414905219308
Item no GF	35001070610
Item no GTIN	06414905219308
Item no LVI	1720784
Item no NOBB	55172672
Item no NRF	5114531
Item no RSK	1899459
Item no VVS	045483035

Dimensions

Item Unit Height	52.2
Item Unit Length	49
Item Unit Weight	0,241
Item Unit Width	46.7
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905468737
Packaging GTIN PL2	06414905442829
Packaging GTIN PL4	06414905499663
Packaging Height PL1	57

Packaging Height PL2	89
Packaging Height PL4	678
Packaging Length PL1	54
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Quantity PL4	1920
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000160056
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,242
Packaging Weight PL2	2,449
Packaging Weight PL4	504
Packaging Width PL1	52
Packaging Width PL2	135
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+