Product data sheet



GF Uponor S-Press tool Mini2 with KSP0 jaw 16/20/25/32

1083586

- Uponor S-Press tool Mini² supplied in carrying case, complete with battery and charger unit and pressing jaws.
- Range of application up to 32 mm.

- Technical specifications:
- Very quick pressing thanks to short pressing cycle of 3-4 seconds
- Crimping force: linear thrust of approx. 15 kN
- Battery capacity: High-power Makita 1.3 Ah Li-Ion battery (3.0 Ah optional)
- Charging time: 1.5 Ah 15 min. 3.0 Ah 22 min
- Weight incl. battery: without jaws 1.7 kg
- Dimensions tool: 377 x 75 x 116 mm
- Revolving/rotatable: approx. 350° rotating pressing jaw holder





Application information GF Uponor S-Press tool Mini2 with KSP0 jaw

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press tool Mini2 with KSP0 jaw 16/20/25/32

1083586





Product code

Item no EAN	4021598131767
Item no GF	35001083586
Item no GTIN	04021598131767
Item no LVI	1725905
Item no NOBB	48959135
Item no NRF	5071293
Item no RSK	1881873
Item no VVS	045498450

Dimensions

Item Unit Height	85
Item Unit Length	380
Item Unit Weight	6,6
Item Unit Width	460
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905469703
Packaging GTIN PL4	06414900310215
Packaging Height PL1	122
Packaging Height PL4	1000
Packaging Length PL1	490
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	30
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,023912
Packaging Volume PL4	0,96
Packaging Weight PL1	6,7
Packaging Weight PL4	223
Packaging Width PL1	400
Packaging Width PL4	800

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+