Product data sheet



GF Uponor S-Press battery Mini2

1083605

- Battery 18 V / 1.5 Ah, Li-Ion (27 Wh)
- Battery voltage: 18 V
- Battery capacity: 1.5 Ah
- Charging time: With SPI S-Press Battery Charger: 15 min
- Cell technology: Li-Ion
- Weight: 0,4 kg





Application information GF Uponor S-Press battery Mini2

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press battery Mini2

1083605





Product code

Item no EAN	4021598131804
Item no GF	35001083605
Item no GTIN	04021598131804
Item no LVI	1725907
Item no NOBB	48959184
Item no NRF	5071295
Item no RSK	1881874
Item no VVS	045498460

Dimensions

Item Unit Height	43
Item Unit Length	114
Item Unit Weight	0,352
Item Unit Width	72
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905469741
Packaging Height PL1	110
Packaging Length PL1	205
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00349525
Packaging Weight PL1	0,517
Packaging Width PL1	155

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+