Product data sheet



GF Uponor S-Press battery UP110

1083608

- Battery 18 V / 3,0 Ah, Li-Ion (54 Wh)
- Charging time: With SPI S-PRESS BATTERY CHARGER: 22 min
- Weight: 0,6 kg





Application information GF Uponor S-Press battery UP110

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:
Male and female threads acc.to EN 10226-1.

GF Uponor S-Press battery UP110

1083608





Product code

Item no EAN	4021598131811
Item no GF	35001083608
Item no GTIN	04021598131811
Item no LVI	1725911
Item no NOBB	48959192
Item no NRF	5071296
Item no RSK	1881875
Item no VVS	045498461

Dimensions

Item Unit Height	62
Item Unit Length	110
Item Unit Weight	0,602
Item Unit Width	75
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905469758
Packaging GTIN PL3	06414905630011
Packaging Height PL1	110
Packaging Height PL3	280
Packaging Length PL1	205
Packaging Length PL3	400
Packaging Quantity PL1	1
Packaging Quantity PL3	10
Packaging Type PL1	Base_Box
Packaging Type PL3	Box

Packaging Volume PL1	0,0033825
Packaging Volume PL3	0,0448
Packaging Weight PL1	0,766
Packaging Weight PL3	7,224
Packaging Width PL1	150
Packaging Width PL3	400

Documents

Page with all documents

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+