


GF Uponor Smatrix Wave thermostat, standard T-165 POD RAL9016

1086981

- measures perceived room temperature
- protection class: IP30
- color: white glossy
- Functions:
 - light indication behind dial after changing the set point
 - heating/cooling demand indication
 - dip switch to enable/disable timer function if timer installed
 - optional: enable/disable timer function
- Consisting of:
 - Uponor Smatrix Wave thermostat standard T-165 POD
 - 2x AAA batteries
 - mounting material



Application information GF Uponor Smatrix Wave thermostat, standard T-165 POD

Specification

- modular system includes controller, expansion module, com module with app for mobile devices, relay modules, thermostats and sensors
- wireless connections with Smatrix Wave thermostats
- up to 8 room thermostats and 10 actuators (24V) per controller
- up to 14 room thermostats and 16 actuators (24V) per controller with expansion module
- up to 4 controllers in one system, wireless connected
- pump and boiler relays (output) with every controller
- 4 outputs in total for systems with relay module M-161, configurable via app
- heating/cooling switch input
- heating/cooling change with thermostat T-267
- relative humidity control with thermostats and sensors
- combines underfloor heating/cooling and ceiling cooling control
- app for mobile devices with installation wizard and intuitive user interface
- on-site access with Bluetooth BLE for commissioning and service
- generating installation configurations for repeated use in the app
- remote access via app for internet connected systems
- Smatrix AI for energy savings in installations with heat pumps
- schedule settings, via app or programmable thermostat T-168
- comfort settings
- shut-off function for the seasonal transitional period
- valve and pump exercise
- fast automatic software updates
- supply diagnostics for internet connected systems
- color LEDs on controller providing status information
- operating voltage of controller 230V
- low voltage actuators: 24VAC /0.2A (0.4A peak)

Application


- wireless room temperature control for radiant heating and cooling
- set point range: +5°C ... +35°C

Certification

- CE, UKCA

GF Uponor Smatrix Wave thermostat, standard T-165 POD RAL9016

1086981

**Product code**

Item no EAN	4021598149113
Item no GF	35001086981
Item no GTIN	04021598149113
Item no LVI	2024501
Item no NOBB	51166742
Item no NRF	8361081
Item no RSK	2987788
Item no VVS	466251021

Dimensions

Item Unit Height	25
Item Unit Length	80
Item Unit Weight	0,108
Item Unit Width	80
Item_UOM	pce

Measurements

LENGTH_L	80
Z Measurement h	25
Z Measurement w	80

Packaging

Packaging GTIN PL1	06414905284627
Packaging GTIN PL3	06414905284634
Packaging GTIN PL4	06414905284641
Packaging Height PL1	40
Packaging Height PL3	300
Packaging Height PL4	1500
Packaging Length PL1	100
Packaging Length PL3	400

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL3	75
Packaging Quantity PL4	1800
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00036
Packaging Volume PL3	0,036
Packaging Volume PL4	1,44
Packaging Weight PL1	0,134
Packaging Weight PL3	10,87
Packaging Weight PL4	285,88
Packaging Width PL1	90
Packaging Width PL3	300
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com