


Uponor Uni Pipe PLUS white insulated S4 WLS 040 32x3,0 blue 50m

1091716

- coil
- Insulation thickness 4 mm
- thermal conductivity $\lambda=0,040 \text{ W/m}^{\circ}\text{K}$
- round extruded



Application information Uponor Uni Pipe PLUS white insulated S4 WLS 040

Specification

- Oxygen diffusion resistant multi-layer composite pipe (PE-RT - adhesive – seamless aluminium/longitudinally welded aluminium - adhesive - PE-RT) produced using SACP and OWC-technology.
- Fire classification E according to EN 13501-1.
- With pipe end caps as hygienic seal according EN 806.

Application


- Tested/Approved according EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar
- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor Uni Pipe PLUS white insulated S4 WLS 040 32x3,0 blue 50m

1091716

**Product code**

Item no EAN	6414905223497
Item no GF	35001091716
Item no GTIN	06414905223497

Dimensions

Item Unit Height	40
Item Unit Length	1000
Item Unit Weight	0,42
Item Unit Width	40
Item_UOM	m

Measurements

Length	50
Outer Diameter_do	32
Outer Diameter_di	26
Wall thickness_s	3
Wall thickness_s1	4

Packaging

Packaging GTIN PL1	06414905269570
Packaging GTIN PL4	06414900394130
Packaging Height PL1	1140
Packaging Height PL4	1500
Packaging Length PL1	1140
Packaging Length PL4	1130
Packaging Quantity PL1	50
Packaging Quantity PL4	400
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,266418

Packaging Volume PL4	1,91535
Packaging Weight PL1	23,83
Packaging Weight PL4	188
Packaging Width PL1	205
Packaging Width PL4	1130

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com