

Uponor Vario M manifold flowmeter 0-5l/min

1121531

- Flowmeter for plastic manifold Vario M
- 0-5 l/min.
- with mechanical stop during opening/closing position



Application information Uponor Vario M manifold flowmeter

Specification

- Made of fibre glass reinforced polyamid
- With integrated valves
- Connection right or left G1 with flat sealing
- Supply bar with flowmeter for balancing and shut-off
- Return bar with return valves and caps
- Integrated airvents and fill&drain points in supply and return
- Loop connection: G3/4" eurocone
- Loop pitch: 50 mm

Application

- For underfloor heating and cooling
- Max. pressure: 6 bar at 60°C
- Combineable with actuators FT 30x1,5

Uponor Vario M manifold flowmeter 0-5l/min

1121531

**Product code**

Item no EAN	6414905660360
Item no GF	35001121531
Item no GTIN	06414905660360

Dimensions

Item Unit Height	93
Item Unit Length	26
Item Unit Weight	0,025
Item Unit Width	28
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905663484
Packaging GTIN PL2	06414905663514
Packaging Height PL1	170
Packaging Height PL2	60
Packaging Length PL1	150
Packaging Length PL2	190
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,000714
Packaging Volume PL2	0,001824
Packaging Weight PL1	0,029
Packaging Weight PL2	0,33
Packaging Width PL1	28
Packaging Width PL2	160

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E
communications@georgfischer.
com