

GF Silenta Premium branch 45° 135-135mm

1146398

- Light gray, PP-material with inorganic filler, according to EN 1451



Application information GF Silenta Premium branch 45°

Specification

- Three-layer polypropylene pipe system manufactured according to EN 1451
- Sound-insulated construction with enhanced mechanical strength
- Pipe diameter range: DN 58 to DN 200
- High chemical and temperature resistance
- Complete system including pipes, fittings and accessories

Application

- Residential buildings and apartment complexes
- Hotels, hospitals, schools and office buildings
- Sustainable and green buildings
- Industrial facilities (short and long-term wastewater use)
- Domestic sewage systems
- Wastewater from kitchens, bathrooms, laundry rooms and sanitary areas

GF Silenta Premium branch 45° 135-135mm

1146398



Status

Item Available From date

2026-02-01

Product code

Item no EAN	8698652133898
Item no GF	4501213530221
Item no GTIN	08698652133898
Item no VVS	186843017

Dimensions

Item Unit Height	343
Item Unit Length	160
Item Unit Weight	2,217
Item Unit Width	303
Item_UOM	pce

Measurements

Length (l2)	68
Z Measurement d1	135
Z Measurement d2	135
Z Measurement e	5,3
Z Measurement L1	68

Packaging

Packaging GTIN PL1	06414900554107
Packaging GTIN PL2	06414900050845
Packaging GTIN PL4	06414900215299
Packaging Height PL1	343
Packaging Height PL2	360
Packaging Height PL4	1200
Packaging Length PL1	160
Packaging Length PL2	390

Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	2
Packaging Quantity PL4	48
Packaging Type PL1	Piece
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,01662864
Packaging Volume PL2	0,040716
Packaging Volume PL4	1,152
Packaging Weight PL1	2,217
Packaging Weight PL2	4,434
Packaging Weight PL4	131,416
Packaging Width PL1	303
Packaging Width PL2	290
Packaging Width PL4	800

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

E
communications@georgfischer.
com