


## GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

**1149459**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: male thread



### Application information GF JRGUMAT thermostatic mixing valve 3400 40°C

#### Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

#### Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

## GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

1149459



### Product code

Item no EAN	7613263101440
Item no GF	350760012
Item no GTIN	07613263101440
Item no RSK	4927925
Item no VVS	723481012

### Dimensions

Item Unit Height	154.5
Item Unit Length	180
Item Unit Weight	3,51
Item Unit Width	94.5
Item_UOM	pce

### Measurements

Length (l1)	70
Length (l2)	110
Z Measurement h1	60
Z Measurement h2	85
Z Measurement h3	70

### Packaging

Packaging GTIN PL1	06414900057646
Packaging Height PL1	126
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00807534
Packaging Weight PL1	3,82
Packaging Width PL1	221

## Documents

Page with all documents



### Uponor Corporation

Ilmalantori 4  
00240, Helsinki  
Finland

T +358 (0)20 129 211

[www.uponor.com](http://www.uponor.com)