


GF JRGUMAT thermostatic mixing valve 3400 55°C DN32**1149483**

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: male thread

**Application information GF JRGUMAT thermostatic mixing valve 3400 55°C****Specification**


- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3400 55°C DN32

1149483



Product code

Item no EAN	7613263100160
Item no GF	350760213
Item no GTIN	07613263100160
Item no RSK	4927919

Dimensions

Item Unit Height	127
Item Unit Length	130
Item Unit Weight	1,59
Item Unit Width	60
Item_UOM	pce

Measurements

Length (l1)	52
Length (l2)	78
Z Measurement h1	41
Z Measurement h2	75
Z Measurement h3	52

Packaging

Packaging GTIN PL1	06414900169325
Packaging Height PL1	102
Packaging Length PL1	220
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00406164
Packaging Weight PL1	1,81
Packaging Width PL1	181

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com