


GF JRGUMAT thermostatic mixing valve 3410 40°C DN80

1149530

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: flange



Application information GF JRGUMAT thermostatic mixing valve 3410 40°C

Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- Potable water systems with requirements for constant mixed water temperature
- Central and decentralized hot water mixing for single- and multi-family homes, hospitality buildings and sports facilities
- Excess-temperature protection in systems using alternative forms of energy such as solar systems

GF JRGUMAT thermostatic mixing valve 3410 40°C DN80

1149530



Measurements

Inner_diameter_di	80
Length (l1)	155
Length (l2)	310
Length (l3)	124
Z Measurement h1	92
Z Measurement h2	127

Product code

Item no EAN	7613263101488
Item no GF	350767415
Item no GTIN	07613263101488

Dimensions

Item Unit Height	282.5
Item Unit Length	310
Item Unit Weight	27,5
Item Unit Width	200
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900169707
Packaging Height PL1	230
Packaging Length PL1	420
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,034293
Packaging Weight PL1	27,8911001199972
Packaging Width PL1	355

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211

www.uponor.com